

**WHAT IS CLAIMED IS:**

1. An active pixel image sensor comprised of a plurality of pixels, at least one pixel comprising:

a photodetector;

a transistor;

a charge to voltage conversion region coupled to said photodetector and connected to the input of said transistor; and

a capacitor connected in parallel with the charge to voltage conversion region wherein the capacitor is designed to have a low voltage coefficient.

2. The device in claim 1, wherein said capacitor provides a capacitance independently of a voltage on said charge to voltage conversion node.

3. The device in claim 1, wherein said capacitor comprises a polysilicon to polysilicon double plate capacitor.

4. The device in claim 1, wherein said capacitor comprises a polysilicon to metal interconnect double plate capacitor.

5. The device in claim 1, wherein said capacitor comprises a metal interconnect to metal interconnect double plate capacitor.

6. An active pixel image sensor comprised of a plurality of pixels, at least one pixel comprising:

a photodetector;

a transistor;

said photodetector also operating as a charge to voltage conversion region connected to the input of said transistor; and

09750745.12900  
006221 5425250

a capacitor connected in parallel with photodetector wherein the capacitor is designed to have a low voltage coefficient.

7. The device in claim 6, wherein said capacitor provides a capacitance independently of a voltage on said charge to voltage conversion node.

8. The device in claim 6, wherein said capacitor comprises a polysilicon to polysilicon double plate capacitor.

9. The device in claim 6, wherein said capacitor comprises a polysilicon to metal interconnect double plate capacitor.

10. The device in claim 6, wherein said capacitor comprises a metal interconnect to metal interconnect double plate capacitor.

11. An active pixel image sensor comprised of a plurality of pixels, at least one pixel comprising:

a photodetector;

a transistor;

a charge to voltage conversion region coupled to said photodetector and connected to the input of said transistor; and

wherein said transistor is configured to operate as a common source amplifier.

12. An active pixel image sensor comprised of a plurality of pixels, at least one pixel comprising:

a photodetector;

a transistor;

a charge to voltage conversion region coupled to said photodetector and connected to the input of said transistor;

006221 5425250

wherein said transistor is configured to operate as a common source amplifier; and

a capacitor connected in parallel with the charge to voltage conversion region wherein the capacitor is designed to have a low voltage coefficient.

005227" 5403460